

Z-1 MONITOR



Cromemco

Specialists in computer peripherals

2432 Charleston Rd., Mountain View, CA 94043 • (415) 964-7400

CROMEMCO Z-1 MONITOR
Copyright 1976 by CROMEMCO
1K Version

The Z-1 Monitor makes it possible to control computers which use the CROMEMCO ZPUTM from a terminal keyboard.

It includes executive commands to examine and change memory, make a binary or an ASCII dump of memory, move and compare blocks of memory, output a byte of data to any port, read and write binary paper tapes, and program 2708 and 2704 proms using the CROMEMCO BYTESAVER.

Transfer of control to a program in memory can be commanded from the keyboard with up to five breakpoints set and with the initial contents of the ZPU registers specified. When a breakpoint is encountered during execution, control is transferred back to the monitor and the contents of all 22 ZPU registers are stored and displayed. These register values can be examined and changed before execution of the program is resumed.

The Z-1 Monitor was designed to be flexible as well as powerful. For example, the monitor does not require the user to address a RAM board at a special place in memory for its own use. Rather, it finds the highest page of RAM active in the machine and places its stack and temporary storage area there. (The top 4AH or 74 bytes of this page should be reserved for system use.)

The monitor is also flexible in its command format. It will accept command words of any length, but it only looks at the first and last characters typed in. This allows the use of either longer expressions for their mnemonic value or shorter expressions for their brevity. For example, any of the following

DR
DISPLAYR
DSPR

causes the contents of all 22 user-registers to be displayed on the terminal.

Many of the commands apply to a range of memory. For example:

MOV 2408 240A B000

will move the contents of locations 2408 through 240A to B000 through B003. Another way to accomplish the same thing is by means of the swath-operator. Thus:

MOV 2408 S3 B000

will move to B000 a swath of 3 bytes starting at 2408.

The format is free-form with respect to spaces.

MOV 2408 S 3 B000
MOV 2408S3 B000
MV 2408S3 B000

All have the same effect. Note that at least one space follows the command word and at least one space separates a pair of numeric operands such as '3' and 'B000'.

USE OF THE MONITOR

Set the power-on jump switch on the ZPU card to E (1110 binary). Whenever the computer is reset control will then immediately pass to the monitor.

If the ZPU is installed in the CROMEMCO Z-1TM computer, depress CARRIAGE RETURN from 2 to 3 times. This will set the UART on the serial interface card to the baud rate of the terminal being used.

When used with a serial interface card with baud rate fixed to that of the terminal, simply depress CARRIAGE RETURN twice. The monitor will respond

CROMEMCO MON1.0 C.1976

followed by a prompt ':'. The monitor is then ready to accept commands from the keyboard.

When entering an address as the operand of a command, only the last four digits typed in are retained. For example:

12345

is read as

2345.

Therefore, if a wrong digit is entered, continue typing until the last four digits are correct. There is a hazard with this, however. An extra 'F' inadvertently typed when '1FFF' is desired yields 'FFFF' instead.

When a two digit number, such as a data byte is entered, only the last two digits typed are retained.

If the monitor detects an error condition, the command is aborted, a '?' is printed followed by the prompt ':' for the next command.

Any command may be aborted from the keyboard either when the monitor is requesting further input, or during print-out, by depressing ESCAPE. For teletypes ESCAPE is the same as CONTROL-SHIFT-K. For most other terminals it is CONTROL SEMI-COLON.

Two cautions should be noted. When using the MOV or the PRGM commands, be careful not to overwrite the system stack and temporary storage area which resides in the upper 4AH or 72 bytes of active RAM installed in the machine.

When the computer is reset, the monitor is also reset. If a user program is executing at the time with breakpoints set, then these breakpoints will remain in the user program until removed by hand. (The normal procedure is for the monitor to restore the user program code whenever a breakpoint is executed.)

The monitor assumes that data transfer occurs on I/O port 1. Status flags are transmitted over input port 0. The Data Available Flag is on bit 6 of input port 0. The Transmitter Buffer Empty flag is on bit 7 of input port 0.

COMMANDS

1. DSPM (Start) (Stop) (CARRIAGE RETURN)

Display memory (DM is the short form) starting with location Start and ending with Stop. As with all 2-operand commands, the swath-operator may be used instead.

DSPM (Start) S (Swath width) (CR).

Example: :DSPM 100 S 3
0100: AB 34 7F

2. DSPR (CR)

Display registers (DR). The 22 registers are displayed with the following format:

00PC	00SP					
0AOF	0B0C	0D0E	0H0L	0I0T	00IX	00IY
AAFF	BBCC	DDEE	HHLL			

where the placement of a 1-byte register, such as A is indicated by "0A", of a 2-byte register, such as the program counter, PC, by "00PC", and of a primed register, such as A' by "AA". The T register, by the way, contains 1 if interrupts were enabled when the monitor was entered, and 0 otherwise.

3. GO (CR)

Resumes execution at the location contained in the user program counter, PC.

GO (Addr) (CR)

Begins execution at Addr.

4. GO/(bpl) (Bp2)...(CR)

Resumes execution at the location of PC with breakpoints set Bpl, Bp2,(Up to 5 breakpoints may be set.)

GO (Addr)/(Bpl)(Bp2)...(CR)

Begins execution at Addr with the indicated breakpoints set. All breakpoints are cleared upon re-entry of the monitor from a breakpoint.

5. MOV (Start) (Stop) (Destination) (CR)

Move (MV) the contents of memory beginning with Start and ending with Stop to Destination. After the move, the monitor verifies that source and destination are the same. This will result in a print-out of discrepancies which are not really errors after certain types of overlapping moves. However, this print-out can be terminated by depressing ESCAPE.

The MOV command can be used to fill a block of memory with a constant. For example, to enter zeros between locations 100 and 10D, use the SBSM command to enter 0 at location 100, and then move 100 through 10C to 101:

MOV 100 10C 101

Care should be taken not to overwrite the system stack which resides in the upper 4AH or 74 bytes of active RAM.

6. OUT (Data Byte) (Port)

Output (OT) Data Byte to Port. One use of this command is

to select banks on CROMEMCO memory boards. When the monitor is first entered on power-up or reset, it selects bank 0 and turns off all other memory banks.

Either a software output or a monitor output to port 40 hex serves to change the bank selection. To select bank n output a byte with bit n high.

<u>Bank</u>	<u>Output byte</u>
0	01
1	02
2	04
3	08
4	10
5	20
6	40
7	80

For example, the following command selects bank 4

OUT 10 40

7. PRGM (Source) (Source-end) (Destination)

Program (PM) from Source through Source-end into proms beginning at Destination.

If the length of the source is not a multiple of 400H (1024 decimal) or if the destination does not begin at a 400H boundary, the monitor will reject the command. (Multiples of 400H end in 000, 400, 800, or C00.)

8. READ (Start) (Stop) (CR)

Read (RD) input from paper tape reader or console and store in memory beginning at Start.

9. SUBM (Addr) (SPACE)

Substitute memory (SM). Displays the contents of Addr and outputs a DOT, '.', as a prompt for the substituted value. If no change is desired, type another '.'. Otherwise, enter the new value. The monitor accepts hex digits until it gets a delimiter, such as a SPACE or DOT, retaining the last 2 digits entered as the value. After it receives a delimiter, the monitor outputs the contents of the next sequential memory location with a DOT prompt. To terminate, depress ESCAPE.

10. SUBR (Register) (SPACE)

Where Register may be PC, SP, A, F, B, C, D, E, H, L, I, T (Interrupts-enabled state), X (IX), Y (IY), A', B', C', D', E', F', H', or L'.

Substitute register (SR). This works like the Substitute - memory command with two exceptions. (1) When substituting for the value of a 2-byte register, the monitor retains the last 4 digits before the delimiter, and (2) after accepting the substitution value for one register, it awaits entry of the ID of the next register.

11. VRFY (Start) (Stop) (Destination) (CR)

Verify (VY) that the block of memory between Start and Stop contains the same values as the block beginning at Destination. The address and contents are printed for each discrepancy found.

12. WRIT (Start) (Stop) (CR)

Write (WT) the contents of memory locations between Start

and Stop on the console or paper tape punch. This is useful for punching binary or ASCII paper tapes of the contents of memory, and for looking at the ASCII contents of memory on the console.

When punching a paper tape, it is often desirable to punch a series of nulls as a leader. This can be done by filling about 60 hex bytes preceding the desired memory block with zeros (see the MOV command) and writing out the whole thing beginning with the nulls. (Depress CARRIAGE RETURN at the end of the WRIT command before turning on the paper-tape punch in order to avoid punching an extra CARRIAGE RETURN, LINE FEED, RUB-OUT at the beginning of the tape.

CROMEMCO Z-1 MONITOR SOURCE LISTING

E000	0005	*			
E000	0006	PPAGE	EQU	OE1H	;MUST BE THE HIGHER OF
E000	0007	*	A PAIR OF	NON-RAM PAGES.	
E000	0010	PSW	EQU	6	
E000	0015	SP	EQU	6	
E000	0016	PF	EQU	80H	;PRIME-ABLE REG FLAG
E000	0017	R2F	EQU	40H	;2-BYTE REG FLAG
E000	0020	BELL	EQU	07	
E000	0025	ESC	EQU	1BH	
E000	0030	CR	EQU	ODH	
E000	0035	LF	EQU	0AH	
E000	0040	STAT	EQU	0	
E000	0045	DAV	EQU	40H	
E000	0050	TBE	EQU	80H	
E000	0055	DATA	EQU	1	
E000	0060	TEMPS	EQU	16H	;ROOM FOR TEMP STORAGE
E000	0065	RSTLC	EQU	30H	;RST LOCATION
E000	0070	CASE	EQU	20H	;DIFF BETW LOWER & UPPER CA
E000	0075	*			
E000	0080	*	Z80 OP-CODES		
E000	0085	JR	EQU	18H	
E000	0090	JRC	EQU	38H	
E000	0095	JRNC	EQU	30H	
E000	0100	JRZ	EQU	28H	
E000	0105	JRNZ	EQU	20H	
E000	0110	DJNZ	EQU	10H	
E000	0115	EXAF	EQU	08	;EX AF,AF
E000	0120	EXX	EQU	0D9H	
E000	0125	RLD	EQU	0EDH	
E000	0130	RLDI	EQU	6FH	
E000	0135	CPI	EQU	0EDH	
E000	0140	CPII	EQU	0A1H	
E000	0145	CPIR	EQU	0EDH	
E000	0150	CPIRI	EQU	0B1H	
E000	0155	LDI	EQU	0EDH	
E000	0160	LDII	EQU	0A0H	
E000	0165	LDIR	EQU	0EDH	
E000	0170	LDIRI	EQU	0B0H	
E000	0175	LDD	EQU	0EDH	
E000	0180	LDI	EQU	0A8H	
E000	0185	LDDR	EQU	0EDH	
E000	0190	LDDR1	EQU	0B8H	
E000	0195	SET5A	EQU	OCBH	
E000	0200	ST5A1	EQU	0EFH	
E000	0205	*			
E000	0210	IX	EQU	0DDH	
E000	0215	IY	EQU	0FDH	
E000	0220	*			

E000 0225 * DISPLACEMENTS FROM IX OF HI BYTE OF REG PAIRS
E000 0230 DUPC EQU 0
E000 0235 DUSP EQU -2
E000 0240 DUAF EQU -4
E000 0245 DUBC EQU -6
E000 0250 DUDE EQU -8
E000 0255 DUHL EQU -10
E000 0260 DUIT EQU -12 *USER I & INTERRUPT ENABLE
E000 0265 DUXI EQU -14
E000 0270 DUYI EQU -16
E000 0275 DUAF2 EQU -18
E000 0280 DUBC2 EQU -20
E000 0285 DUDE2 EQU -22
E000 0290 DUHL2 EQU -24
E000 0295 *
E000 0300 *,START
E000 0305 * ENTER MONITOR FROM RESET
E000 0310 *
E000 0315 *
E000 0320 * ORG 0E000H
E000 0325 *
E000 3E 01 0330 MVII A,J
E002 D3 40 0335 OUT 40H ;SELECT BANK 0
E004 0340 *
E004 0345 * PLACE SYS STACK AT HIGHEST PAGE OF
E004 0350 * AVAILABLE RAM.
E004 0355 * ALLOW ROOM FOR TEMP STORAGE.
E004 0360 *
E004 21 EB 00 0365 LXI H,00FFH-TEMPS+2
E007 25 0370 INIT DCR H
E008 7E 0385 MOV A,M
E009 34 0390 INR M
E00A BE 0395 CMP M ;DID IT CHANGE?
E00B 28 0400 DB JRZ
E00C FA 0405 DB INIT-\$-1
E00D 35 0410 DCR M ;YES. RESTORE IT.
E00E 0415 *
E00E 0440 * HL NOW POINTS TO BP STACK END
E00E 0445 *
E00E 36 00 0455 MVII M,O ;BP STACK END MARK
E010 7D 0465 MOV A,L ;SAVE
E011 2B 0470 DCX H ;STORAGE FOR BPSP,LO
E012 77 0475 MOV M,A ;STORE BPSP,LO
E013 11 E6 FF 0480 LXI D,DUHL2-2
E016 19 0481 DAD D ;TO END OF REG STORAGE
E017 F9 0482 SPHL ;SYS SP
E018 0483 *
E018 ED 0484 DB OEDH ;SBC HL,DE; BACK TO UPC,HI
E019 52 0485 DB 52H ;(CY WAS SET BY 'DAD D')
E01A E5 0486 PUSH H
E01B DD 0487 DB IX
E01C E1 0488 POP H ;POP IX;STORAGE PNTR
E01D 0489 *
E01D 16 E1 0490 MVII D,PPAGE ;FORCE USER SP TO
E01F 2B 0491 DCX H
E020 2B 0492 DCX H
E021 72 0493 MOV M,D ;POINT TO PROM
E022 0495 *

E022	0500	*	SET BAUD RATE	
E022	0505	*		
E022 3E D8	0510	INITI	MVI A,0D8H	;300 BAUD
E024 CD 36 E0	0515	CALL	BAUD	
E027 3E F4	0520	MVI	A,0F4H	;110 BAUD
E029 C4 36 E0	0525	CNZ	BAUD	
E02C 20	0537	DB	JRNZ	
E02D F4	0538	DB	INITI-\$-1	
E02E	0540	*		
E02E 21 94 E3	0545	LXI	H,HEAD	;HEADING
E031 CD 0C E2	0550	CALL	PMSG	
E034	0555	*		
E034 18	0560	DB	JR	
E035 .66	0565	DB	CMND-\$-1	
E036	0566	*		
E036	0567	*		
E036 D3 00	0568	BAUD	OUT STAT	;SET BAUD RATE
E038 CD 41 E1	0569	CALL	GBYTE	
E03B CD 41 E1	0570	CALL	GBYTE	;CAN WE
E03E E6 7F	0571	ANI	7FH	;READ
E040 FE 0D	0572	CPI	CR	;A CR?
E042 C9	0573	RET		
E043	0575	*		
E043	0580	*	ENTER MONITOR FROM BRKPT	
E043	0585	*		
E043	0590	*	SAVE MACHINE STATE. SAVES ALL REGS INCLUDING	
E043	0595	*	SP, FINDS THE TOP OF RAM INSTALLED IN MACHINE	
E043	0600	*	& SWITCHES THE STACK THERE.	
E043	0605	*		
E043 E3	0610	SVMS	XTHL	;ADJUST BRKPT RET ADDR
E044 2B	0615	DCX	H	
E045 E3	0620	XTHL		
E046	0625	*		
E046 E5	0630	PUSH	H	;SAVE
E047 21 04 00	0635	LXI	H,4	
E04A 39	0640	DAD	SP	;USP (USER-SP)
E04B E3	0645	XTHL		;TO STACK
E04C	0650	*		
E04C F5	0655	PUSH	PSW	;UAF
E04D C5	0660	PUSH	B	;UBC
E04E D5	0665	PUSH	D	;UDE
E04F E5	0670	PUSH	H	;UHL
E050	0675	*		
E050	0680	*	FIND SYS STACK AGAIN	
E050	0685	*		
E050 21 E9 00	0690	LXI	H,00FFH-TEMPS	
E053 25	0695	SVMS1	DCR H	;DECRM MEM PAGE
E054 7E	0710	MOV	A,M	
E055 34	0715	INR	M	
E056 BE	0720	CMP	M	;DID IT CHANGE?
E057 28	0725	DB	JRZ	
E058 FA	0730	DB	SVMS1-\$-1	

E059 35	0735	DCR	M	YES. RESTORE IT.
E05A	0740 *			
E05A EB	0745	XCHG		
E05B 21 0B 00	0750	LXI	H,11	
E05E 39	0755	DAD	SP	*PNTS TO BPRA, HI BYTE
E05F 01 0C 00	0760	LXI	B,12	
E062 ED	0765	DB	LDDR	*TRANSFER TO SYS STACK
E063 B8	0770	DB	LDDR1	
E064 13	0775	INX	D	*DE HAS CURRENT VALUE OF
E065	0780 *	SYS SP AND POINTS TO UR		
E065 23	0785	INX	H	*HL HAS CURRENT VALUE OF
E066	0790 *	USER SP AND ALSO POINTS TO UR		
E066 EB	0795	XCHG		
E067 F9	0800	SPHL		*SYS SP
E068	0805 *			
E068 ED	0810	DB	OEDH	*LD A,I
E069 57	0815	DB	57H	
E06A 0E 00	0820	MVI	C,0	
E06C E2 70 E0	0825	JPO	SVMS3	*IFF?
E06F OC	0830	INR	C	
E070	0835 *	C NOW HOLDS	USER-IFF	
E070 47	0840	SVMS3	MOV B,A	
E071 C5	0845	PUSH	B	*UIF (USER-I & USER-IIFF)
E072	0850 *			
E072 DD	0855	DB	IX	
E073 E5	0860	PUSH	H	*PUSH IX; UIX
E074 FD	0865	DB	IY	
E075 E5	0870	PUSH	H	*PUSH IY; UIY
E076 01 0B 00	0875	LXI	B,DUPC-DUHL+1	
E079 09	0880	DAD	B	*PNTS TO UPC, HI BYTE
E07A E5	0885	PUSH	H	
E07B DD	0890	DB	IX	
E07C E1	0895	POP	H	*TO IX (POINTS TO UPC)
E07D	0900 *			
E07D 08	0905	DB	EXAF	
E07E F5	0910	PUSH	PSW	
E07F D9	0915	DB	EXX	
E080 C5	0920	PUSH	B	*UBC2
E081 D5	0925	PUSH	D	*UDE2
E082 E5	0930	PUSH	H	*UHL2
E083	0935 *			
E083	0940 *			
E083 DD	0945	DB	IX	
E084 E5	0950	PUSH	H	*PUSH IX
E085 E1	0955	POP	H	
E086 23	0960	INX	H	*POINTS TO BPSP,LO
E087 6E	0965	MOV	L,M	*BPSP NOW IN HL
E088	0970 *			
E088	0975 *	CLEAR ALL BRKPTIS		
E088	0980 *			

E088 7E	0985 CLBP1	MOV	A,M	:BP STK EMPTY?
E089 B7	0990 ORA		A	
E08A 28	0995 DB		JRZ	
E08B 0A	1000 DB			CLBP2-\$-1
E08C	1005 *			
E08C 2B	1010 DCX		H	
E08D 56	1015 MOV		D,M	
E08E 2B	1020 DCX		H	
E08F 5E	1025 MOV		E,M	
E090 2B	1030 DCX		H	
E091 7E	1035 MOV		A,M	
E092 12	1040 STAX	D		:RESTORE CONTENTS TO MEM
E093 2B	1045 DCX		H	
E094 18	1050 DB		JR	
E095 F2	1055 DB			CLBP1-\$-1
E096	1060 *			
E096 7D	1065 CLBP2	MOV	A,L	
E097 2B	1070 DCX		H	
E098 77	1075 MOV	M,A		:ADJUST @PSP
E099	1080 *			
E099 CD F5 E0	1120 CALL	DSPR		:DISPLAY USER REGISTERS
E09C	1125 *			
E09C	1130 *	GET 1-BYTE COMMAND.		
E09C	1135 *	RETURNS VALUE IN HL & JUMPS TO THAT ADDR.		
E09C	1140 *			
E09C CD OC E1	1145 CMND	CALL	CRLF	
E09F 21 B3 E3	1147 CMND1	LXI	H,PRMPT	
E0A2 CD OC E2	1150	CALL	PMMSG	
E0A5	1155 *	HL NOW PNTS TO TBL ADDR		
E0A5 CD 1A E2	1160	CALL	GCMND	:DE GETS LETTER - 'A'
E0A8 EB	1165	XCHG		
E0A9 29	1170 DAD	H		:TIMES 2
E0AA 19	1175 DAD	D		: + TBL ADDR
E0AB 5E	1180 MOV	E,M		
E0AC 23	1185 INX	H		
E0AD 56	1190 MOV	D,M		
E0AE EB	1195 XCHG			
E0AF 11 9F E0	1200 LXI	D,CMND1		:SET UP RETURN
E0B2 D5	1205 PUSH	D		:TO CMND
E0B3 79	1207 MOV	A,C		:A & C HAVE CMND DELIMITER
E0B4 E9	1210 PCHL			
E0B5	1215 *			
E0B5	1416 *			
E0B5	1417 *			
E0B5	1418 *	REJECTS ALL BUT ALPHABETIC CHARACTERS.		
E0B5	1419 *	RETURNS THE CHAR LESS THE ASCII VALUE OF 'A'.		
E0B5	1420 *			
E0B5 D6 61	1421 ABCYZ	SUI	'A'+CASE 'A' OR ABOVE?	
E0B7 38	1422 DB		JRC	
E0B8 03	1423 DB		ERROR-\$-1	
E0B9 FE 19	1424 CPI	25D		: 'Y' OR BELOW?
E0BB D8	1425 RC			: IF NOT, CONTINUE BELOW

EOBC	1426	*		
EOBC	1427	*		
EOBC	1430	*	ERROR & ESCAPE. RETURNS TO CMND WITH SP	
EOBC	1435	*	POINTING TO SAVED-REG AREA (UHL2).	
EOBC	1440	*		
EOBC CD 09 E2	1445	ERROR	CALL	PSQS ;PRINT ' ? <BELL>'
EOBF DD	1450	ESCAPE	DB	IX
EOC0 E5	1455		PUSH	H ;PUSH IX
EOC1 E1	1460		POP	H
EOC2 11 E7 FF	1465		LXI	D,DUHL2-1-DUPC
EOC5 19	1470		DAD	D
EOC6 F9	1475		SPHL	
EOC7 18	1480		DB	JR
EOC8 D3	1485		DB	CMND-\$-1 ;GET NEW CMND
EOC9	1490	*		
EOC9	1495	*		
EOC9	1530	*	PROGRAM PROMS. ABORTS IF DESTINATION	
EOC9	1535	*	IS NOT ON A 1K (400H) BOUNDARY, SWATH	
EOC9	1540	*	WIDTH IS NOT A MULTIPLE OF 1K.	
EOC9	1550	*		
EOC9	1570	*		
EOC9 06 B5	1575	PROG	MVI	B,181 ;360 ITERATIONS
EOCB C5	1580	PROG1	PUSH	B ;SAVE # OF ITERATIONS
EOCC CD 70 E1	1590		CALL	LD2N ;SOURCE TO DE, INCRM TO BC,
E●CF F5	1595		PUSH	PSW ;SAVE LATEST DELIMITER
EOD0 78	1600		MOV	A,B ;IS INCRM A MULT OF 1024?
EOD1 E6 03	1605		ANI	3
EOD3 B1	1610		ORA	C
EOD4 20	1615		DB	JRNZ
EOD5 E6	1620		DB	ERROR-\$-1
EOD6 F1	1623		POP	PSW ;LAST DELIMITER
EOD7 CD 8E E1	1625		CALL	LINCR ;SOURCE TO HL, DEST TO DE
EODA 7A	1635		MOV	A,D ;IS DEST A MULT OF 1024?
EODB E6 03	1640		ANI	3
EODD B3	1645		ORA	E
EODE 20	1650		DB	JRNZ
EODF DC	1655		DB	ERROR-\$-1
EOEO	1660	*		
EOE0 F1	1665	PROG3	POP	PSW ;ITERATIONS
EOE1 F5	1670		PUSH	PSW
EOE2 C5	1675		PUSH	B ;INCREMENT
EOE3 01 00 04	1685		LXI	B,1024
EOE6 C5	1687		PUSH	B ;SAVE
EOE7 CD 50 E2	1690		CALL	MVE ;MOVE IT
EOEA C1	1691		POP	B ;RETRIEVE
EOEB E3	1730		XTHL	;INCRM TO HL
EOEC B7	1737		ORA	A ;RESET CY
EOED ED	1740		DB	0EDH ;SBC HL,BC
EOEE 42	1745		DB	42H
EOEF E3	1750		XTHL	;SOURCE BACK TO HL
EOFO C1	1755		POP	B ;NEW INCRM

EOF1 20	1760	DB	JRNZ	
EOF2 ED	1765	DB	PROG3-\$-1	!LOOP IF INCRM NOT 0
EOF3 F1	1767	POP	PSW	;CLEAN UP
EOF4 C9	1775	RET		;BACK TO CMND
EOF5	1780 *			
EOF5	1782 *	COMMAND		
EOF5	1785 *			
EOF5	1800 *	DISPLAY THE USER REGISTERS.		
EOF5	1805 *			
EOF5 CD OC E1	1810	DSPR CALL	CRLF	
EOF8 DD	1815	DB IX		
EOF9 E5	1820	PUSH H		;PUSH IX
E0FA E1	1825	POP H		;POINTS TO UPC
EOFB 06 02	1830	MVI B,2		;UPC & USP
EOFD CD 07 E1	1835	CALL PREGS		
E100 06 07	1840	MVI B,7		;UAF THRU UIY
E102 CD 07 E1	1845	CALL PREGS		
E105 06 04	1850	MVI B,4		;UAF2 THRU UHL2
E107 CD 4A E1	1855	PREGS CALL	P2BMS	;PRINT 2 BYTES PNTED TO B
E10A 10	1860	DB DJNZ		
E10B FB	1865	DB PREGS-\$-1		
E10C	1870 *	(CONTINUE BELOW)		
E10C	1875 *			
E10C	1880 *			
E10C	1885 *	PRINT CR & LF. PRESERVES ALL REGS BUT A.		
E10C	1890 *			
E10C 3E 0D	1895	CRLF MVI A,CR		
E10E	1900 *	(CONTINUE BELOW)		
E10E	1905 *			
E10E	1910 *			
E10E	1915 *	PRINT THE CHARACTER IN THE A-REGISTER. (CHECKS		
E10E	1920 *	INPUT FOR ESCAPE.) PRESERVES ALL REGS.		
E10E	1925 *			
E10E F5	1930	PCHR PUSH PSW		;SAVE THE CHAR
E10F DB 00	1935	IN STAT		
E111 E6 40	1940	ANI DAV		
E113 28	1945	DB JRZ		
E114 08	1950	DB PCHR2-\$-1		
E115 DB 01	1955	IN DATA		
E117 E6 7F	1960	ANI 7FH		
E119	1965 *			
E119 FE 1B	1970	PCHR1 CPI ESC		
E11B 28	1975	DB JRZ		
E11C A2	1980	DB ESCPE-\$-1		
E11D	1985 *			
E11D DB 00	1990	PCHR2 IN STAT		
E11F E6 80	1995	ANI TBE		
E121 28	2000	DB JRZ		
E122 FA	2005	DB PCHR2-\$-1		
E123 F1	2010	POP PSW		
E124 D3 01	2015	OUT DATA		

E126 F5	2020	PUSH	PSW
E127 E5	2025	PUSH	H
E128 21 B0 E3	2030	LXI	H,LFNN
E12B FE 0D	2035	CPI	CR
E12D CC 0C E2	2040	CZ	PMMSG
E130 E1	2045	POP	H
E131 F1	2050	POP	PSW
E132 C9	2055	RET	
E133	2060 *		
E133	2065 *		
E133	2070 *	GET CHARACTER. RETURNS IT IN A. CONVERTS	
E133	2075 *	ALPHA CHARS TO LOWER-CASE. ALTERS F.	
E133	2080 *		
E133 CD 41 E1	2085 GCHR	CALL	GBYTE
E136 E6 7F	2087 ANI		7FH
E138 FE 41	2090 CPI		'A'
E13A 38	2095 DB		JRC
E13B 02	2100 DB		GCHR1-\$-1
E13C F6 20	2105 ORI		20H ;CONVERT TO LOWER-CASSE
E13E F5	2110 GCHR1	PUSH	PSW ;SAVE THE CHAR
E13F 18	2112 DB		JR
E140 D8	2115 DB		PCHR1-\$-1 ;PRINT IT
E141	2116 *		
E141	2117 *		
E141 DB 00	2118 GBYTE	IN	STAT
E143 E6 40	2119 ANI		DAV
E145 28	2120 DB		JRZ
E146 FA	2121 DB		GBYTE-\$-1
E147 DB 01	2122 IN		DATA
E149 C9	2123 RET		
E14A	2124 *		
E14A	2125 *	PRINT 2 BYTES IN (HL) & (HL - 1).	
E14A	2130 *	DECREMENTS HL BY 2. ALTERS A. PRESERVES OTHERS	
E14A	2135 *		
E14A CD E5 E1	2140 P2BMS	CALL	PNM
E14D 2B	2145 DCX		H
E14E CD E5 E1	2150 CALL		PNM
E151 2B	2155 DCX		H
E152	2160 *		
E152	2165 *		
E152	2170 *	PRINTS SPACE. PRESERVES ALL REGS BUT A.	
E152	2175 *		
E152 3E 20	2180 SPACE	MVI	A,20H
E154 18	2185 DB		JR
E155 B8	2190 DB		PCHR-\$-1
E156	2195 *		
E156	2200 *		
E156	2205 *	IF HL IS A MULTIPLE OF 16, DO PADDR.	
E156	2210 *		
E156 3E 0F	2215 CK16B	MVI	A,15
E158	2220 *		
E158	2225 *		

E158 2230 * ENTER WITH A CONTAINING N. IF HL IS A MUL-
E158 2235 * TIPLE OF N+1, DO PADDR.
E158 2240 *
E158 A5 2245 CKBND ANA L
E159 C0 2250 RNZ
E15A 2255 *
E15A 2260 *
E15A 2265 * PRINT THE NUMBER IN HL, FOLLOWED BY A COLON.
E15A 2270 * PRESERVES ALL REGS EXCEPT A.
E15A 2275 *
E15A CD OC E1 2280 PADDR CALL CRLF
E15D CD DA E1 2285 PADR1 CALL PNHL
E160 3E 3A 2290 MVI A,^{/*}
E162 18 2295 DB JR
E163 AA 2300 DB PCHR-\$-1
E164 2305 *
E164 2310 *
E164 2325 * LOAD TWO NUMBERS. FOLLOW WITH A CRLF.
E164 2330 *
E164 CD 70 E1 2335 L2NCR CALL LD2N
E167 2340 *
E167 2345 * SKIP INITIAL SPACES.
E167 2350 * IF DELIMITTER NOT A CR, ERROR
E167 2355 *
E167 CD D1 E1 2360 SKSGC CALL SKSG ;LOOK FOR A NON-SPACE
E16A FE OD 2365 CPI CR ;CR?
E16C C2 BC EO 2370 JNZ ERROR
E16F C9 2375 RET
E170 2380 *
E170 2385 *
E170 2390 * LOAD TWO NUMBERS. LOADS DE WITH THE BEGINNING
E170 2395 * ADDR, NI. LOADS BC & HL WITH THE INCREMENT
E170 2400 * N2-N1+1 (OR WITH N2 IF THE OPR IS 'S').
E170 2405 * RETURNS WITH LAST DELIMITTER IN A.
E170 2420 *
E170 2440 *
E170 CD 97 E1 2455 LD2N CALL GNHL ;NI TO HL, DELIMITTER TO A
E173 EB 2460 XCHG ;SAVE NI IN DE
E174 CD D1 E1 2465 CALL SKSG ;GET NEXT NON-SPACE CHAR
E177 FE 73 2475 CPI 'S'+CASE ;SWATH?
E179 20 2476 DB JRNZ
E17A 06 2477 DB LD2N1-\$-1
E17B 2478 *
E17B AF 2480 XRA A ;YES
E17C CD 97 E1 2485 CALL GNHL ;INCREMENT TO HL
E17F 18 2505 DB JR
E180 07 2510 DB LD2N2-\$-1
E181 2511 *
E181 CD 97 E1 2512 LD2N1 CALL GNHL ;INCREMENT
E184 B7 2513 ORA A ;CLEAR CY
E185 ED 2515 DB OEDH ;SBC HL,DE

E186	52	2520	DB	52H	;N2-N1
E187	23	2525	INX	H	;INCLUDE END POINT
E188	44	2550	LD2N2	MOV	B,H
E189	4D	2555	MOV	C,L	;BC GETS THE INCRM
E18A	C9	2565	RET		
E18B		2570	*		
E18B		2575	*		
E18B		2580	*	LOAD 3 OPERANDS. HL GETS SOURCE, DE THE	
E18B		2585	*	3RD OPERAND, BC THE INCREMENT & A THE	
E18B		2590	*	LOW BYTE OF THE 3RD OPERAND.	
E18B		2595	*		
E18B	CD 70 E1	2600	LD3N	CALL	LD2N
E18E		2605	*	(CONTINUE BELOW)	
E18E		2610	*		
E18E		2615	*		
E18E		2620	*	TRANSFER DE TO HL. ENTER WITH SPACE OR	
E18E		2625	*	1ST DIGIT OF NUMBER IN A. GET NUMBBR	
E18E		2630	*	INTO DE WITH LOW BYTE ALSO TO A.	
E18E		2635	*	FINISHES WITH A CRLF.	
E18E		2640	*		
E18E	CD 97 E1	2645	LINCR	CALL	GNHL ;SKIP SPACES, LOAD HL
E191	CD 67 E1	2650		CALL	SKSGC ;WAIT FOR A CR
E194	7D	2655		MOV	A,L
E195	EB	2660		XCHG	
E196	C9	2665		RET	
E197		2670	*		
E197		2675	*		
E197		2680	*	CLEAR HL. IF ENTERED WITH HEX CHAR IN A,	
E197		2685	*	SHIFTS IT INTO HL. O/W, IGNORES LEADING	
E197		2690	*	SPACES. FIRST CHAR MUST BE HEX. CONTINUES	
E197		2695	*	SHIFT UNTIL A NON-HEX CHAR RECEIVED & THEN	
E197		2700	*	RETURNS WITH THE LATTER IN A.	
E197		2715	*	PRESERVES B,C,D,E.	
E197		2720	*		
E197		2730	*		
E197	C5	2735	GNHL	PUSH	B ;SAVE
E198	21 00 .00	2740	GNHL1	LXI	H,0 ;CLEAR BUFFER
E19B		2745	*	STRIP LEADING SPACES & GET CHAR	
E19B	CD D1 E1	2750		CALL	SKSG
E19E		2760	*	FIRST CHAR MUST BE HEX	
E19E	CD AF E1	2785		CALL	HEXSH ;IF HEX, SHIFT INTO HL
E1A1	DA BC E0	2790		JC	ERROR ;O/W, RETRY
E1A4	CD 33 E1	2795	GNHL3	CALL	GCHR
E1A7	CD AF E1	2840	GNHL5	CALL	HEXSH ;IF HEX SHIFT INTO HL
E1AA	78	2845		MOV	A,B ;RESTORE CHAR
E1AB	30	2850		DB	JRNC
E1AC	F7	2855		DB	GNHL3-\$-1 ;IF HEX, CONTINUE
E1AD	C1	2860		POP	B ;IF NON-HEX, DONE
E1AE	C9	2865		RET	
E1AF		2870	*		

EIAF 2875 *

EIAF 2880 * IF A CONTAINS HEX CHAR, SHIFTS BINARY EQUIVALENT INTO HL. IF NOT HEX, RET WITH CY SET. SAVES

EIAF 2885 *

EIAF 2890 * ORIGINAL CHAR IN B

EIAF 2895 *

EIAF 47 2900 HEXSHH MOV B,A

EIB0 D6 30 2905 SUI '0' ; < '0'?

EIB2 D8 2910 RC

EIB3 C6 C9 2915 ADI '0'--G--CASE

EIB5 D8 2920 RC

EIB6 D6 FA 2925 SUI 'A'--G'

EIB8 30 2930 DB JRNC 1OK IF >= 'A'

EIB9 03 2935 DB HXSHO-\$-1

EIBA C6 27 2940 ADI 'A'-'9'--1+CASE

EIBC D8 2945 RC

EIBD C6 0A 2950 HXSHO DW OAC6H ;ADI 29+1-0

EIBF 2955 * THE A-REG NOW CONTAINS THE HEX DIGIT IN BINARY

EIBF 2960 * (THE HIGH-ORDER NIBBLE OF A IS 0.)

EIBF CD C8 E1 2965 HXSH4 CALL HXSH1 ;SHIFT 4 BITS INTO HL

EIC2 CD C8 E1 2970 CALL HXSH1

EIC5 CD C8 E1 2975 CALL HXSH1

EIC8 2980 *

EIC8 07 2985 HXSH1 RLC ;SHIFT INTO BIT 4

EIC9 29 2990 DAD H ;SHIFT LEFT

EICA 2995 * CLEAR CY IN CASE OF RET FROM HEXSH

EICA B7 3000 ORA A

EICB CB 3005 DB OCBH ;BIT 4,A

EICC 67 3010 DB 67H ;IS IT 0?

EICD C8 3015 RZ

EICE 23 3020 INX H

EICF C9 3025 RET

EIDO 3030 *

EIDO 3035 *

EIDO 3040 * RETURNS WITH A NON-SPACE IN THE A-REG.

EIDO 3045 * IF ENTERED WITH A-REG CONTAINING A NULL

EIDO 3050 * OR A SPACE, GETS NEW CHARS UNTIL FIRST

EIDO 3055 * NON-SPACE OCCURS. ALTERS AF.

EIDO 3060 *

EIDO AF 3065 SKSG0 XRA A ;START WITH A NULL

EID1 3070 *

EID1 B7 3075 SKSG ORA A ;DOES A CONTAIN NULL?

EID2 CC 33 E1 3080 SKSG1 CZ GCHR

EID5 FE 20 3085 CPI 20H ;SPACE?

EID7 28 3090 DB JRZ

EID8 F9 3095 DB SKSG1-\$-1

EID9 C9 3100 RET

EIDA 3105 *

EIDA 3110 *

EIDA 3330 *

EIDA 3335 *

E1DA
E1DA
E1DA F5
E1DB E5
E1DC CD EB E1
E1DF E1
E1E0 F1
E1E1 C9
E1E2
E1E2
E1E2
E1E2 CD 52 E1
E1E5
E1E5
E1E5
E1E5
E1E5
E1E5 F5
E1E6 CD F3 E1
E1E9 F1
E1EA C9
E1EB
E1EB
E1EB
E1EB 21 03 00
E1EE 39
E1EF CD F3 E1
E1F2 2B
E1F3
E1F3
E1F3
E1F3
E1F3
E1F3 7E
E1F4 0F
E1F5 0F
E1F6 0F
E1F7 0F
E1F8 CD FC E1
E1FB 7E
E1FC E6 0F
E1FE FE OA
E200 38
E201 02
E202 C6 07
E204 C6 30

3350 * PRINT THE NUMBER IN HL. PRESERVES ALL REGS.
3355 *
3360 PNHL PUSH PSW
3365 PUSH H ;TO STACK
3370 CALL P4HEX
3375 POP H
3380 POP PSW
3385 RET
3390 *
3395 *
3400 * PRINT SPACE FOLLOWED BY THE NUMBER POINTED
3405 * TO BY HL. ALTERS A ONLY.
3410 *
3415 PSNM CALL SPACE
3420 * (CONTINUE BELOW)
3425 *
3430 * PRINTS THE NUMBER POINTED TO BY HL.
3435 * PRESERVES ALL RDGISTDRS.
3440 *
3445 PNM PUSH PSW
3450 CALL P2HEX
3455 POP PSW
3460 RET
3465 *
3470 *
3475 * PRINTS 4 HEX CHARS FROM TOP OF STACK.
3480 * ALTERS F,H,L.
3485 *
3490 P4HEX LXI H,3
3495 DAD SP ;HL = SP
3505 CALL P2HEX ;HIGH BYTE
3510 DCX H ;LOW BYTE
3515 *
3520 *
3525 * PRINT THE NUMBER POINTED TO BY HL.
3530 * PRESERVES ALL REGS EXCEPT AF.
3535 *
3540 P2HEX MOV A,M ;GET THE NUMBER
3545 RRC
3550 RRC
3555 RRC
3560 RRC
3565 CALL P1HEX ;LEFT NIBBLE
3570 MOV A,M ;NOW DO THE RIGHT NIBBLE
3575 P1HEX ANI OFH ;MASK
3580 CPI 10 ; <= 9?
3585 DB JRC
3590 DB P1HX1-\$-1
3595 ADI 7 ;A THRU F
3600 P1HX1 ADI 30H ;ASCII BIAS

E206 C3 0E E1	3605	JMP	PCHR	:PRINT IT
E209	3615	*		
E209	3620	*		
E209	3625	*	PRINT MESSAGE. ENTER WITH ADDR OF MSG	
E209	3630	*	IN HL. MSG IS TERMINATED BY 00 THRU 07.	
E209	3635	*	PRESERVES FLAGS, CLEARS A, INCRM HL.	
E209	3640	*		
E209	3645	*		
E209	3650	*	PRINT ' ? <BELL>'	
E209	3655	*		
E209 21 AD E3	3660	PSQS	LXI	H,SQS
E20C	3665	*		
E20C 3E 00	3670	PMSG	MVI	A,O :CLEAR A (FOR GNHL)
E20E F5	3675	PUSH	PSW	:SAVE FLAGS
E20F 7E	3680	PMSG1	MOV	A,M
E210 23	3685	INX	H	
E211 CD 0E E1	3690	CALL	PCHR	
E214 E6 F8	3695	ANI	OF8H	:<NULL> THRU <BELL>?
E216 20	3700	DB	JRNZ	
E217 F7	3705	DB	PMSG1-\$-1	
E218 F1	3710	POP	PSW	
E219 C9	3715	RET		
E21A	3720	*		
E21A	3725	*		
E21A	3980	*		
E21A	3985	*		
E21A	3990	*	DE GETS THE FIRST ALPHA CHAR - 'A'.	
E21A	3991	*	C GETS THE FIRST DELIMITER.	
E21A	3992	*	B IS INITIALIZED TO '0' & RETURNS	
E21A	3993	*	THE LAST CMND CHARACTER.	
E21A	3994	*		
E21A CD D0 E1	3995	GCMND	CALL	SKSGO :GET NON-SPACE
E21D CD B5 E0	3996		CALL	ABCYZ :ALPHA CHECK
E220 5F	3997		MOV	E,A
E221 16 00	3998		MVI	D,O :DE HAS TBL DISPLACEMENT
E223 06 6F	3999		MVI	B,'0'+CASE :INITIALIZE FOR GO CMND
E225 CD 33 E1	4000	GCMN1	CALL	GCHR :GET CHAR
E228 FE 30	4002		CPI	30H :DELIMITER ?
E22A 4F	4004		MOV	C,A :DELIM STORE
E22B D8	4006		RC	:IF SO, DONE
E22C 47	4008		MOV	B,A :LAST CHAR STORE
E22D 18	4010		DB	JR
E22E F6	4015		DB	GCMN1-\$-1
E22F	4045	*		
E22F	4050	*		
E22F	4065	*	COMMAND	
E22F	4070	*		
E22F CD 8B E1	4075	VERIF	CALL	LD3N :GET 3 OPERANDS
E232	4080	*		
E232	4085	*		
E232	4090	*	COMPARES TWO AREAS OF MEMORY. ENTER WITH	
E232	4095	*	SOURCE IN HL. DESTINATION IN DE & COUNT	

E232 * IN BC. ALTERS ALL REGISTERS.
E232 1A 4105 VRFY LDAX D ;DESTINATION
E233 ED 4110 DB CPI ;COMPARE TO SOURCE
E234 A1 4115 DB CPII ;
E235 C4 OC E1 4120 CNZ CRLF ;IF NOT SAME, CRLF
E238 2B 4125 DCX H ;(CPI INCRMS HL)
E239 C4 DA E1 4130 CNZ PNHL ; & PRINT SOURCE ADDR
E23C C4 E2 E1 4135 CNZ PSNM ; & SOURCE CONTENTS
E23F EB 4140 XCHG ;
E240 C4 E2 E1 4145 CNZ PSNM ; & DEST CONTENTS
E243 EB 4150 XCHG ;
E244 23 4155 INX H ;RESTORE HL FOR CPI
E245 13 4160 INX D ;NEXT DEST
E246 E2 OC E1 4165 JPO CRLF ;IF BC = 0, DONE
E249 18 4170 DB JR ;
E24A E7 4175 DB VRFY-\$-1
E24B 4180 *
E24B 4185 *
E24B 4190 * COMMAND
E24B 4195 *
E24B CD 8B E1 4200 MOVE CALL LD3N ;OPERANDS
E24E 3E 01 4210 MVI A, I ;# OF ITERATIONS
E250 4215 *
E250 4220 *
E250 4225 * MOVE FROM ONE LOCATION TO ANOTHER. ENTER
E250 4230 * WITH SOURCE ADDR IN HL, DEST IN DE, BYTE
E250 4235 * COUNT IN BC. THE MOVE IS ITERATED N TIMES,
E250 4240 * WHERE N = TWICE THE CONTENTS OF A, LESS ONE.
E250 4245 * INCREMENTS HL & DE BY BC. CHECKS RESULT
E250 4250 * & PRINTS THE ERRORS FOUND.
E250 4255 *
E250 37 4260 MVE STC ;CY IS USED IN ITERATION COU
E251 E5 4265 MVE1 PUSH H ;SOURCE
E252 D5 4270 PUSH D ;DEST
E253 C5 4275 PUSH B ;BYTE COUNT
E254 F3 4280 DI ;FOR PROM PROGRAMMING
E255 ED 4285 DB LDIR ;ONE ITERATION
E256 B0 4290 DB LDIRI ;
E257 FB 4295 EI ;
E258 C1 4300 POP B ;
E259 D1 4305 POP D ;
E25A E1 4310 POP H ;
E25B 4315 * ITERATION CALCULATIONS
E25B 3F 4320 CMC ;
E25C 38 4325 DB JRC ;
E25D F3 4330 DB MVE1-\$-1 ;
E25E 3D 4335 DCR A ;
E25F 20 4340 DB JRNZ ;
E260 F0 4345 DB MVE1-\$-1 ;
E261 4350 * CHECK RESULT

E261	18	4355	DB	JR
E262	CF	4360	DB	VRFY-\$-1
E263		4364	*	
E263		4365	*	
E263		4367	* COMMAND	
E263		4368	*	
E263		4370	* GO <CR>	EXECUTION BEGINS AT USER PC.
E263		4375	*	
E263		4376	* COMMAND	
E263		4377	*	
E263		4380	* GO <ADDR1>/<ADDR2> ... <ADDRN>	
E263		4385	* EXECUTION BEGINS AT ADDR1 WITH BREAKPOINTS SET	
E263		4390	* AT ADDR2,...,ADDRN.	
E263		4395	*	
E263	78	4400	GO	MOV A,B ;CHECK THAT THE LAST
E264	FE 6F	4401	CPI	'0'+CASE ;CMND CHAR IS '0'
E266	C2 BC EO	4402	JNZ	ERROR
E269	79	4403	MOV	A,C ;CMND DELIMITER
E26A	0E 00	4405	MVI	C,O ;BP FLAG
E26C	CD D1 E1	4410	G01	CALL SKSG ;WAIT FOR NON-SPACE
E26F	FE OD	4415	CPI	CR
E271	28	4420	DB	JRZ
E272	3A	4425	DB	RETN-\$-1 ;RETN IF CR
E273	FE 2F	4430	CPI	'/' ;BP?
E275	20	4435	DB	JRNZ
E276	0E	4440	DB	G03-\$-1
E277	0E 01	4445	MVI	C,I ;SET BRKPT FLAG
E279	21 30 00	4450	LXI	H,RSTLC ;TRANSFER
E27C	36 C3	4455	MVI	M,OC3H ;JMP SVMS TO
E27E	21 43 EO	4460	LXI	H,SVMS
E281	22 31 00	4465	SHLD	RSTLC+1 ;RST LOC
E284	AF	4468	XRA	A
E285	CD 97 E1	4470	G03	CALL GNHL ;GET ADDR
E288	CB 41	4475	DW	41CBH ;BIT O,C: FLAG SET?
E28A	EB	4478	XCHG	
E28B	28	4480	DB	JRZ
E28C	18	4485	DB	G05-\$-1 ;JMP IF NO BP
E28D	DD	4495	DB	IX
E28E	E5	4500	PUSH	H ;PUSH IX
E28F	E1	4505	POP	H
E290	23	4510	INX	H
E291	6E	4515	MOV	L,M ;HL = BPSP
E292		4520	*	
E292	23	4525	INX	H ;BUMP BPSP
E293	EB	4530	XCHG	;DE=BPSP, HL= BP ADDR
E294	46	4535	MOV	B,M ;CONTENTS
E295	36 F7	4537	MVI	M,OC7H+RSTLC ;RST INSTRUCTION
E297	EB	4540	XCHG	;HL=BPSP
E298	70	4545	MOV	M,B ;TO BP STACK
E299	23	4550	INX	H ;BUMP BPSP

E29A	73	4555	MOV	M,E	;BP ADDR TO STACK	
E29B	23	4560	INX	H		
E29C	72	4565	MOV	M,D		
E29D	23	4570	INX	H		
E29E	36 01	4575	MVI	M,01	;PUNCTUATION (BP SET)	
E2A0	DD	4580	DB	IX		
E2A1	75	4585	MOV	M,L	;LD (IX+1),L	
E2A2	01	4590	DB	I		
E2A3	18	4592	DB	JR		
E2A4	C7	4593	DB	G01-\$-1		
E2A5		4595	* CHANGE USER	PC		
E2A5	DD	4600	G05	DB	IX	
E2A6	72	4605	MOV	M,D	;LD (IX+DUPC),D	
E2A7	00	4610	DB	DUPC		
E2A8	DD	4615	DB	IX		
E2A9	73	4620	MOV	M,E	;LD (IX+DUPC-1),E	
E2AA	FF	4625	DB	DUPC-1		
E2AB	18	4630	DB	JR		
E2AC	BF	4635	DB	G01-\$-1	;BACK FOR MORE	
E2AD		4640	*			
E2AD	E1	4645	RETN	POP	H	;STRIP CMND ADDR FROM STK
E2AE	E1	4650		POP	H	;UHL2
E2AF	DI	4655		POP	D	;UDE2
E2B0	CI	4660		POP	B	;UBC2
E2B1	F1	4665		POP	PSW	;UAF2
E2B2	D9	4670		DB	EXX	
E2B3	08	4675		DB	EXAF	
E2B4	FD	4680		DB	IY	
E2B5	E1	4685		POP	H	;POP IY; UIY
E2B6	DD	4690		DB	IX	
E2B7	E1	4695		POP	H	;POP IX; UIX
E2B8		4700	*			
E2B8	F1	4705		POP	PSW	;UIF
E2B9	ED	4710		DB	OEDH	
E2BA	47	4715		DB	47H	;LD I,A; UI
E2BB	F3	4720		DI		
E2BC	30	4725		DB	JRNC	
E2BD	01	4730		DB	RETN1-\$-1	
E2BE	FB	4735		EI		
E2BF		4740	*IFF NOW RESTORED			
E2BF	E1	4745	RETN1	POP	H	;UHL
E2C0	DI	4750		POP	D	;UDE
E2C1	CI	4755		POP	B	;UBC
E2C2	F1	4760		POP	PSW	;UAF
E2C3	E3	4765		XTHL		;USP TO HL, UHL TO (SP)
E2C4	F5	4770		PUSH	PSW	
E2C5	C5	4775		PUSH	B	
E2C6	D5	4780		PUSH	D	
E2C7	01 OA 00	4785		LXI	B,10	
E2CA	EB	4790		XCHG		;USP TO DE
E2CB	1B	4795		DCX	D	

E2CC	21	09	00	4800	LXI	H,9	
E2CF	39			4805	DAD	SP	
E2D0	ED			4810	DB	LDLR	TRANSFER UPC THRU UHL, L
E2D1	B8			4815	DB	LDLR	; TO USER STACK
E2D2	EB			4820	XCHG		; IS (USER SP - 1) RAM?
E2D3	7E			4825	MOV	A,M	
E2D4	34			4830	INR	M	
E2D5	BE			4835	CMP	M	; DID IT CHANGE?
E2D6	28			4840	DB	JRZ	
E2D7	03			4845	DB	RETN2-\$-1	
E2D8			*	4850			
E2D8	35			4855	DCR	M	; YES. RESTORE IT.
E2D9	F9			4860	SPHL		; CHANGE TO USER STACK
E2DA	33			4865	INX	SP	; CORRECT FOR LDDR EXTRA DCR
E2DB			*	4866			
E2DB	D1			4870	RETN2	POP	D ; OTHERWISE, CONTINUE SYS
E2DC	C1			4875	POP	B	
E2DD	F1			4880	POP	PSW	
E2DE	E1			4885	POP	H	
E2DF	C9			4890	RET		
E2E0			*	4891			
E2E0			*	4900	*	ENTER WITH HL POINTING TO MEMORY & B CONTAININ	
E2E0			*	4905	*	THE 2-BYTE REG FLAG.	
E2E0			*	4910	*	PRINTS SPACE, CONTENTS OF (HL) & ALSO (HL-1) F	
E2E0			*	4915	*	2-BYTE REGS, GETS SUBSTITUTION VALUE INTO DE,	
E2E0			*	4920	*	WRITES E INTO (HL) OR (HL-1) FOR 2-BYTE REGS.	
E2E0			*	4925	*	RETURNS WITH Z-FLAG RESET IFF A CHANGE IS INDICATED (BY A LACK OF '..') FOR A 2-BYTE REG.	
E2E0			*	4930	*	CATED (BY A LACK OF '..') FOR A 2-BYTE REG.	
E2E0			*	4935	*	PRESERVES BC,HL.	
E2E0			*	4940	*		
E2E0	CD	E2	E1	4945	GSUBV	CALL	PSNM ; PRINT (HL)
E2E3	CB			4950	DB	OCBH	; BIT 6,B
E2E4	70			4955	DB	7OH	; 2-BYTE REG?
E2E5	28			4960	DB	JRZ	
E2E6	04			4965	DB	GSBV1-\$-1	
E2E7	2B			4970	DCX	H	; YES, PRINT
E2E8	CD	E5	E1	4975	CALL	PNM	; LO BYTE
E2EB	3E	2E		4980	GSBV1	MVI	A,'.'
E2ED	CD	0E	E1	4985	CALL	PCHR	
E2F0	CD	33	E1	4990	CALL	GCHR	
E2F3	FE	2E		4995	CPI	'.'	; SUBSTITUTION?
E2F5	CC	0E	E1	5000	CZ	PCHR	; IF NOT, PRINT ANOTHER
E2F8	28			5005	DB	JRZ	
E2F9	08			5007	DB	GSBV2-\$-1	
E2FA	E8			5010	XCHG		
E2FB	CD	97	E1	5015	CALL	GNHL	; NEW VALUE
E2FE	EB			5020	XCHG		; TO DE
E2FF	73			5025	MOV	M,E	; LOAD MEM
E300				5035	*	THE FOLLOWING TEST IS FOR SBSR	
E300	CB			5040	DB	OCBH	; BIT 6,B

E301	70	5045	DB	70H	\$2-BYTE REG?
E302	23	5050	GSBV2	INX H	
E303	C9	5052	RET		
E304		5055	*		
E304		5060	*		
E304		5061	*	COMMAND	
E304		5062	*		
E304		5065	*	SM <ADDR>	SUBSTITUTE MEMORY LOCATION.
E304		5070	*		
E304		5072	*	COMMAND	
E304		5073	*		
E304		5075	*	SR <REGISTER NAME>	SUBSTITUTE USER REGISTER
E304		5080	*		
E304		5085	*	REGISTER NAMES: P (PC), S (SP),	
E304		5090	*	A, F, B, C, D, E, H, L,	
E304		5095	*	I, T (IFF), X (IX), Y (IY),	
E304		5100	*	A', F', B', C', D', E', H', L'.	
E304		5105	*		
E304	78	5110	SUBST	MOV A,B	:LAST CMND CHAR
E305	FE 72	5115		CPI 'R'+CASE	:SR?
E307	79	5117		MOV A,C	:DELIMITER
E308	28	5120		DB JRZ	
E309	0F	5125		DB	SBSR-\$-1
E30A		5130	*		
E30A	CD 97 E1	5135	SBSM	CALL GNHL	:HL GETS ADDR
E30D	06 00	5140	SBSM1	MVI B,0	:REG FLAGS
E30F		5145	*	PRINT CURRENT VALUE, REQUEST NEW VALUE &	
E30F		5150	*	PRINT IT IF GIVEN	
E30F	CD E0 E2	5155		CALL GSUBV	
E312	3E 07	5160		MVI A,7	:8 ENTRIES PER LINE
E314	CD 58 E1	5165		CALL CKBND	
E317	18	5170		DB JR	
E318	F4	5175		DB	SBSM1-\$-1
E319		5180	*		
E319	CD 1A E2	5185	SBSR	CALL GCMND	:DE GETS LETTER - 'A'
E31C	21 E7 E3	5190		LXI H,RGTBL	
E31F	19	5195		DAD D	:PNTS TO REG DISPLACEMENT
E320	42	5200		MOV B,D	:D = 0
E321	CB	5205		DB OCBH	:BIT 7,(HL)
E322	7E	5210		DB 7EH	:A THRU L?
E323	28	5215		DB JRZ	
E324	0C	5220		DB	SBSR1-\$-1
E325	79	5225		MOV A,C	:LAST CMND DELIMITER
E326	FE 20	5230		CPI 20H	:SPACE?
E328	28	5235		DB JRZ	
E329	07	5240		DB	SBSR1-\$-1
E32A	FE 27	5245		CPI ****	:PRIMED?
E32C	C2 BC E0	5250		JNZ	ERROR
E32F	06 0E	5265		MVI B,DUAF-DUAF2	:YES
E331		5270	*		
E331	7E	5275	SBSR1	MOV A,M	:DISPLACEMENT & FLAGS

E332 B7	5277	ORA	A	:IF 0, ILLEGAL CMND
E333 CA BC E0	5278	JZ	ERROR	
E336 E6 1F	5280	ANI	1FH	:STRIP FLAGS OFF
E338 80	5285	ADD	B	:ADJUST FOR PRIMES
E339 5F	5290	MOV	E,A	:DE GETS DISPL (D=0)
E33A 46	5295	MOV	B,M	:SAVE ORIG ENTRY
E33B DD	5300	DB	IX	
E33C E5	5305	PUSH	H	:PUSH IX
E33D E1	5310	POP	H	:STACK FRAME
E33E ED	5315	DB	0EDH	:SBC HL,DE
E33F 52	5317	DB	52H	:PNTS TO USER REG
E340	5320	*	PRINT CURRENT VALUE, DE GETS SUBSTITUTION	
E340	5325	*	VALUE, IF ANY, & (HL) OR (HL-1) GETS E.	
E340	5330	*	Z-FLAG RESET IFF CHANGE FOR A 2-BYTE REG.)	
E340 CD E0 E2	5335	CALL	GSUBV	
E343 28	5340	DB	JRZ	
E344 01	5345	DB	SBSR3-\$-1	
E345 72	5350	MOV	M,D	:NO. HI BYTE
E346 CD 52 E1	5355	SBSR3	CALL	SPACE
E349 18	5360	DB	JR	
E34A CE	5365	DB	SBSR-\$-1	
E34B	5370	*		
E34B	5371	*		
E34B 78	5372	DISPL	MOV	A,B :LAST CMND CHAR
E34C FE 72	5373	CPI	'R'+CASE	:DR?
E34E 79	5374	MOV	A,C	:CMND DELIMITER
E34F CA F5 E0	5375	JZ	DSPR	
E352	5377	*		
E352	5379	*		
E352	5380	*	COMMAND	
E352	5381	*		
E352	5390	*	DISPLAY MEMORY.	
E352	5395	*		
E352 CD 64 E1	5400	DSPM	CALL	L2NCR :INIT DE, INCRM TO BC,
E355	5405	*		:DELIMITER TO A
E355 EB	5410	XCHG		:NI TO HL
E356 CD 5D E1	5415	DSPM1	CALL	PADRI :PRINT ADDR, //
E359 CD E2 E1	5420	DSPM2	CALL	PSNM :PRINT CONTENTS OF MEM
E35C 23	5425	INX	H	
E35D 0B	5430	DCX	B	
E35E 78	5435	MOV	A,B	
E35F B1	5440	ORA	C	:DONE?
E360 CA OC E1	5445	JZ	CRLF	
E363 CD 56 E1	5450	CALL	CK16B	:CHECK FOR 16 COUNT
E366 18	5455	DB	JR	
E367 F1	5460	DB	DSPM2-\$-1	
E368	5465	*		
E368	5470	*		
E368	5475	*	...SUBDM 00 7E 5 585 BY 5	100 DBE++
E368	5500	*		

E368 5505 *

E368 5507 * COMMAND

E368 5510 * READ BINARY INPUT FROM DATA PORT

E368 5512 *

E368 CD 64 E1 5514 READB CALL L2NCR ;GET MEM ADDRS

E36B CD 41 E1 5516 RDB1 CALL GBYTE ;GET INPUT

E36E 12 5518 STAX D ;TO MEM

E36F 13 5520 INX D

E370 0B 5522 DCX B ;COUNT

E371 78 5524 MOV A,B

E372 B1 5526 ORA C ;BC = 0?

E373 20 5528 DB JRNZ

E374 F6 5530 DB RDB1-\$-1

E375 C9 5532 RET

E376 5534 *

E376 5536 *

E376 5537 * COMMAND

E376 5538 * WRITE BINARY OUTPUT TO DATA PORT

E376 5540 *

E376 CD 64 E1 5542 WRITB CALL L2NCR ;GET MEM ADDRS

E379 DB 00 5544 WRTB1 IN STAT

E37B E6 80 5546 ANI TBE

E37D 28 5548 DB JRZ

E37E FA 5550 DB WRTB1-\$-1

E37F IA 5552 LDAX D

E380 D3 01 5554 OUT DATA

E382 13 5556 INX D

E383 0B 5558 DCX B

E384 78 5560 MOV A,B

E385 B1 5562 ORA C

E386 20 5564 DB JRNZ

E387 F1 5566 DB WRTB1-\$-1

E388 C9 5568 RET

E389 5570 *

E389 5572 *

E389 5574 * COMMAND

E389 5576 * OUT <DATA-BYTE> <PORT NNUMBER>

E389 5578 *

E389 CD 97 E1 5580 OUTP CALL GNHL

E38C EB 5582 XCHG ;E GETS DATA

E38D CD 97 E1 5584 CALL GNHL ;GET PORT NUMBER

E390 5585 *

E390 4D 5586 MOV C,L ; TO C

E391 ED 59 5588 DW 59EDH ;OUT (C),E

E393 C9 5590 RET

E394 5591 *

E394 5592 *

E394 OD 5593 HEAD DB CR

E395 OD 5595 DB CR

E396	43 52 4F 4D	5600	ASC	#CROMEMCO MON1.0 C.1976#
	45 4D 43 4F			
	20 4D 4F 4E			
	31 2E 30 20			
	43 2E 31 39			
	37 36			
E3AC	00	5605	DB	0
E3AD		5610 *		
E3AD		5630 *		
E3AD	20 3F	5635 SQS	ASC	;" ?;"
E3AF	07	5640	DB	BELL
E3BO		5645 *		
E3BO	0A	5650 LFNN	DB	LF
E3B1	7F	5655	DB	7FH :NULL
E3B2	00	5660	DB	0
E3B3		5665 *		
E3B3		5690 *		
E3B3	3A	5695 PRMPT	DB	;" "
E3B4	00	5700	DB	0
E3B5		5705 * THE COMMAND TBL MUST IMMEDIATELY FOLLOW		
E3B5		5706 * THE PROMPT MESSAGE		
E3B5	BC E0	5710	DW	ERROR :A
E3B7	BC E0	5715	DW	ERROR :BANK
E3B9	BC E0	5720	DW	ERROR :C
E3BB	4B E3	5725	DW	DISPL :DISPLAY
E3BD	BC E0	5730	DW	ERROR :ENTER
E3BF	BC E0	5735	DW	ERROR :FILE
E3C1	63 E2	5740	DW	GO
E3C3	BC E0	5745	DW	ERROR :H
E3C5	BC E0	5750	DW	ERROR :INPUT
E3C7	BC E0	5755	DW	ERROR :J
E3C9	BC E0	5760	DW	ERROR :K
E3CB	BC E0	5765	DW	ERROR :LIST
E3CD	4B E2	5770	DW	MOVE
E3CF	BC E0	5775	DW	ERROR :NUMBER
E3D1	89 E3	5780	DW	OUTP :OUTPUT
E3D3	C9 E0	5785	DW	PROG :PROGRAM
E3D5	BC E0	5790	DW	ERROR :Q
E3D7	68 E3	5795	DW	READB :READ BINARY OR ASCII
E3D9	04 E3	5800	DW	SUBST :SUBSTITUTE
E3DB	BC E0	5805	DW	ERROR :TRAP
E3DD	BC E0	5810	DW	ERROR :UNEQUAL
E3DF	2F E2	5815	DW	VERIF :VERIFY
E3E1	76 E3	5820	DW	WRITB :WRITE BINARY OR ASCII
E3E3	BC E0	5825	DW	ERROR :X
E3E5	BC E0	5830	DW	ERROR :Y
E3E7		5840 *		
E3E7		5850 *		
E3E7		5851 *		
E3E7	84	5852 RGTBL	DB	-DUAF+PF :A

E3E8 86	5853	DB	-DUBC+PF ;B
E3E9 87	5854	DB	-DUBC+I+PF ;C
E3EA 88	5855	DB	-DUDE+PF ;D
E3EB 89	5856	DB	-DUDE+I+PF ;E
E3EC 85	5857	DB	-DUAF+I+PF ;F
E3ED 00	5858	DB	0
E3EE 8A	5859	DB	-DUHL+PF ;H
E3EF 0C	5860	DB	-DUIT ;I
E3F0 00	5861	DB	0
E3F1 00	5862	DB	0
E3F2 8B	5863	DB	-DUHL+I+PF ;L
E3F3 00	5864	DB	0
E3F4 00	5865	DB	0
E3F5 00	5866	DB	0
E3F6 40	5867	DB	-DUPC+R2F ;PC
E3F7 00	5868	DB	0
E3F8 00	5869	DB	0
E3F9 42	5870	DB	-DUSP+R2F ;SP
E3FA 0D	5871	DB	-DUIT+I ;T (INTERRUPT ENABLE)
E3FB 00	5872	DB	0
E3FC 00	5873	DB	0
E3FD 00	5874	DB	0
E3FE 4E	5875	DB	-DUIX+R2F ;X (IX)
E3FF 50	5876	DB	-DUIY+R2F ;Y (IY)