

TECHNOLOGY: Diode laser, dry
electro-photographic
method

FONTS: Pitch: 10,12,15
Proportional
Courier,Line Printer,
Installable font cards,
Downloadable fonts
Pastes Graphics,
Roman-8 (HP Mode),
IBM-US (HP Mode),
IBM-D/N (HP Mode),
Bold Roman-8 (HP Mode),
Bold IBM-US ((HP Mode),
Bold IBM-D/N (HP Mode),
Bold ECMA-94 (HP Mode),
USA ASCII (All Ex
HP Mode),Courier
Emphasized (Epson Mode)

ATTRIBUTES: Full Cursor control
Automatic Underline
Programmable Macros
Italic (Epson mode)
Double-strike Mode
(Bold), Super/Subscript,
Double-speed/density Bit
Image, Quadruple Density
Bit Image,Condensed,
Compressed

PAPER FEED: Automatic cassette
or manual feed

OPTIONS: Sheet feeder (26-2861)
Envelope feeder
(26-2862),Extra Letter
paper cassette (26-2863)
Legal paper cassette
(26-2860)
1.5 meg memory upgrade
(26-2852),Second sheet
feeder (26-2861),Font
cards (26-2854 to 2859)

DIMENSIONS: 10 1/2 x 13 3/8 x 14 3/16"

FCC CLASS: B, UL Listed
Class I Laser product

SPEED: 6 pages per minute
RESOLUTION: 300 dots per inch
EMULATION: HP LaserJet Series II,
Epson FX-80, IBM Graphics
Printer, IBM Proprinter,
and Diablo 630/630 ECS
INTERFACE: IBM parallel,RS-232C serial
INPUT BUFFERS: 512K expandable to 2MB
PAPER WIDTH: 3 7/8 to 8 1/2"
OF COPIES: 1
CONFIG. SETUP: Front panel LCD
HEAD LIFE: N/A
MTBF: N/A
NOISE LEVEL: 50 dB max. (printing)
45 dB max. (idle)
RIBBON: Toner Cartridge (26-2841)
Developer Cart. (26-2843)
WEIGHT: 33.1 lbs.
POWER: 120 VAC, 50/60 Hz
CONSUMPTION: 650 watts (warm-up)
500 watts (printing)
450 watts (stand-by)